



## Short Link Chain

### mild steel, commercial quality

Not to be used for lifting applications!

- **Material** : mild steel, grade 3
- **Safety factor** : MBL equals 4 x WLL
- **Finish** : self colour or hot dipped galvanised
- **Certification** : works certificates can be supplied on request
- **Note** : the minimum breaking load shown below is for guidance only  
the product is not suitable for lifting purposes

diameter		length inside	width outside	minimum breaking load	weight per metre
inch	a mm	b mm	c mm	kg	kg
3/16	5	19	17	1250	0.50
1/4	6.3	18	20	1600	0.75
5/16	8	24	26	3200	1.35
3/8	10	30	34	5000	1.85
1/2	12.7	36	44	8000	3.80
5/8	16	45	54	12500	5.80
3/4	20	56	67	20000	9.00

## Long Link Chain

### mild steel, commercial quality

Not to be used for lifting applications!

- **Material** : mild steel, grade 3
- **Safety factor** : MBL equals 4 x WLL
- **Finish** : self colour or hot dipped galvanised
- **Certification** : works certificates can be supplied on request
- **Note** : the minimum breaking load shown below is for guidance only  
the product is not suitable for lifting purposes

diameter		length inside	width outside	minimum breaking load	weight per metre
inch	a mm	b mm	c mm	kg	kg
3/16	5	25	21	1000	0.53
1/4	7	38	29	1250	0.63
5/16	8	50	33	2500	1.08
3/8	10	50	38	4000	1.57
1/2	12.7	66	48	6300	2.95
5/8	16	100	60	10000	4.45
3/4	20	125	75	16000	7.00