

Closed Body Rigging Screws - Quality Range

Oval Eye - Oval Eye

- **Material** : high tensile steel
- **Safety factor** : MBL equals 5 x WLL
- **Finish** : hot dipped galvanised or self colour
- **Certification** : as standard a works certificate is supplied
- **Note** : galvanised finish threads are cut after galvanising

diameter thread	length body	length closed position	length open position	diameter	length eye inside	width eye inside	working load limit		weight each
a inch	b mm	c mm	d mm	e mm	f mm	g mm	tons	cwts	kg
1/4	99	169	245	5	10	10		2	0.09
5/16	107	185	287	6	11	11		3	0.16
3/8	152	245	353	8	25	11		7.5	0.35
1/2	229	315	515	10	33	13		10	0.84
5/8	229	370	540	14	39	18		15	1.16
3/4	229	405	555	16	48	22		22	1.83
7/8	305	495	708	17	49	24		32	2.73
1	356	560	798	20	49	24		42	3.55
1 1/8	356	580	828	19	56	28	2	15	4.80
1 1/4	380	640	878	23	68	34	3	15	6.36
1 1/2	405	680	918	26	75	39	5	2	8.10
1 3/4	405	715	933	30	85	40	7		11.40
2	405	760	998	35	100	45	9	5	17.20
2 1/4	405	800	987	43	115	58	11	10	29.00
2 1/2	420	800	1000	48	120	60	15		36.00

Closed Body Rigging Screws - Quality Range

Oval Eye - Jaw

- **Material** : high tensile steel
- **Safety factor** : MBL equals 5 x WLL
- **Finish** : hot dipped galvanised or self colour
- **Certification** : as standard a works certificate is supplied
- **Note** : galvanised finish threads are cut after galvanising

diameter thread	length body	length closed position	length open position	diameter pin	length jaw inside	opening jaw	width jaw	length eye inside	width eye inside	working load limit		weight each
a inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	j mm	k mm	tons	cwts	kg
1/4	99	169	245	5	14	6	12	10	10		2	0.10
5/16	107	185	287	6	16	8	16	11	11		3	0.17
3/8	153	240	350	8	27	12	28	25	11		7.5	0.43
1/2	229	355	530	10	33	14	32	33	13		10	0.92
5/8	229	375	545	13	48	22	40	39	18		15	1.24
3/4	229	395	545	16	50	23	45	48	22		22	1.97
7/8	305	470	683	19	58	28	54	49	24		32	3.04
1	356	550	788	22	60	32	60	49	24		42	4.30
1 1/8	356	560	793	22	75	32	60	56	28	2	15	5.00
1 1/4	380	625	863	25	80	37	75	68	34	3	15	7.39
1 1/2	405	670	918	33	85	49	87	75	39	5	2	10.80
1 3/4	405	700	913	36	110	49	99	85	40	7		14.40
2	405	755	988	42	125	58	108	100	45	9	5	22.20
2 1/4	405	800	998	48	140	70	120	115	58	11	10	36.00
2 1/2	420	810	980	51	135	70	128	120	60	15		44.50

Please note that the 1/4" & 5/16" sizes have round eyes