


Galvanised Turnbuckles Eye - Eye

drop forged



- **Material** : drop forged high tensile steel SAE 1035 or 1045
- **Safety factor** : MBL equals 5 x WLL
- **Standard** : generally to ASTM F1145-92
formerly U.S. Federal Specification FF-T-791b
- **Finish** : hot dipped galvanised
- **Certification** : a works certificate or proof load certificate can be supplied upon request

diameter thread	take up	length closed position	length open position	diameter eye	width inside	length inside	length closed position	working load limit	weight each
a inches	b inches	c mm	c mm	d mm	e mm	f mm	g mm	tons	kg
$\frac{3}{8}$	6	302	454	9	13	28	65	0.54	0.32
$\frac{1}{2}$	6	338	490	12	18	36	80	1.00	0.66
$\frac{1}{2}$	9	414	642	12	18	36	80	1.00	0.76
$\frac{1}{2}$	12	490	795	12	18	36	80	1.00	0.91
$\frac{5}{8}$	6	394	546	14	21	43	98	1.59	1.07
$\frac{5}{8}$	9	470	698	14	21	43	98	1.59	1.31
$\frac{5}{8}$	12	546	851	14	21	43	98	1.59	1.71
$\frac{5}{8}$	18	701	1150	14	21	43	98	1.59	1.86
$\frac{3}{4}$	6	432	584	17	25	53	113	2.36	1.65
$\frac{3}{4}$	9	508	736	17	25	53	113	2.36	1.95
$\frac{3}{4}$	12	584	889	17	25	53	113	2.36	2.30
$\frac{3}{4}$	18	737	1194	17	25	53	113	2.36	2.85
$\frac{7}{8}$	12	625	854	20	31	59	118	3.27	3.33
$\frac{7}{8}$	18	778	1121	20	31	59	118	3.27	4.24
1	6	524	676	22	36	74	155	4.54	3.87
1	12	676	981	22	36	74	155	4.54	5.09
1	18	829	1286	22	36	74	155	4.54	6.00
1	24	980	1592	22	36	74	155	4.54	7.52
$1\frac{1}{4}$	12	760	1055	29	45	88	197	6.90	8.12
$1\frac{1}{4}$	18	912	1370	29	45	88	197	6.90	10.40
$1\frac{1}{4}$	24	1064	1665	29	45	88	197	6.90	12.10
$1\frac{1}{2}$	12	823	1129	32	54	105	215	9.71	12.70
$1\frac{1}{2}$	18	975	1434	32	54	105	215	9.71	15.10
$1\frac{1}{2}$	24	1128	1738	32	54	105	215	9.71	17.10
$1\frac{3}{4}$	18	1060	1533	38	60	119	254	12.70	23.10
$1\frac{3}{4}$	24	1213	1838	38	69	119	254	12.70	26.30
2	24	1315	2011	45	69	146	308	16.78	40.70
$2\frac{1}{2}$	24	1486	2098	51	79	165	344	27.22	64.00
$2\frac{3}{4}$	24	1562	2171	57	83	178	381	34.02	88.00

