


# Galvanised Turnbuckles Jaw - Jaw drop forged



- **Material** : drop forged high tensile steel SAE 1035 or 1045
- **Safety factor** : MBL equals 5 x WLL
- **Standard** : generally to ASTM F1145-92  
formerly U.S. Federal Specification FF-T-791b
- **Finish** : hot dipped galvanised
- **Certification** : a works certificate or proof load certificate can be supplied upon request

diameter thread	take up	length closed position	length open position	opening jaw	length inside	diameter pin	thickness jaw eye	diameter jaw eye	working load limit	weight each
a	b	c	d	e	f	g	h		tons	kg
inches	inches	mm	mm	mm	mm	mm	mm	mm		
3/8	6	302	454	13	22	8	8	21	0.54	0.37
1/2	6	338	490	16	26	9.5	10	25	1.00	0.73
1/2	9	414	642	16	26	9.5	10	25	1.00	0.79
1/2	12	490	795	16	26	9.5	10	25	1.00	0.96
5/8	6	394	546	18	33	13	13	33	1.59	1.37
5/8	9	470	698	18	33	13	13	33	1.59	1.31
5/8	12	546	851	18	33	13	13	33	1.59	1.53
5/8	18	701	1150	18	33	13	13	33	1.59	1.86
3/4	6	432	584	23	38	15.5	16	41	2.36	1.86
3/4	9	508	736	23	38	15.5	16	41	2.36	2.31
3/4	12	584	889	23	38	15.5	16	41	2.36	2.56
3/4	18	737	1194	23	38	15.5	16	41	2.36	3.11
7/8	12	625	854	27	44	19	18	48	3.27	3.71
7/8	18	778	1121	27	44	19	18	48	3.27	4.14
1	6	524	676	30	52	22	20	54	4.54	4.29
1	12	676	981	30	52	22	20	54	4.54	5.07
1	18	829	1286	30	52	22	20	54	4.54	6.62
1	24	980	1592	30	52	22	20	54	4.54	7.85
1 1/4	12	760	1055	44	73	29	25	67	6.90	9.48
1 1/4	18	912	1370	44	73	29	25	67	6.90	11.60
1 1/4	24	1064	1665	44	73	29	25	67	6.90	13.00
1 1/2	12	823	1129	52	70	35	27	80	9.71	13.60
1 1/2	18	975	1434	52	70	35	27	80	9.71	14.30
1 1/2	24	1128	1738	52	70	35	27	80	9.71	18.40
1 3/4	18	1060	1533	59	85	41	33	90	12.70	25.00
1 3/4	24	1213	1838	59	85	41	33	90	12.70	28.70
2	24	1315	2011	64	93	51	39	108	16.78	45.40
2 1/2	24	1486	2098	75	114	57	38	143	27.22	73.00
2 3/4	24	1562	2171	89	110	70	42	156	34.02	98.00

